G 1/2" ELECTRIC HEATING ELEMENTS with plug-in thermostat and T-piece

300 - 1350 W heated towel rails



Z-SKVT Electric Heating Elements

Resistance heating elements intended for heating of static or flowing water, antifreeze fluid or thermal oil in heated towel rails.

They are designed to be installed in any position except for vertical with el. cable upwards. The power supply spiral cable is fitted with Uni Schuko plug.

These heating elements come in a kit with a TZT33 plug-in thermostat and a G 1/2" FFM T-piece, for installation into a heated towel rail connected in a traditional hot-water heating circuit.



Output:

Application:

The heating element is switched on/ off to keep the room temperature at the value set by the rotating knob.

The desired temperature is set by rotating the thermostat control knob.

TECHNICAL DATA

HEATING ELEMENT stainless steel AISI A304
CONNECTION G 1/2" M
HEATING ELEMENT BODY chrome plated brass
POWER SUPPLY 230 V 50 Hz
EL. WIRING 1/N/PE AC 230V
IP RATING IP 44
PROTECTION CLASS BY
EN 61140 ed.2

OPERATING THERMOSTAT fixed setting, automat. reset SWITCH-OFF TEMP. 80 \pm 5 °C SWITCH-ON TEMP. 35 \pm 15 °C

SAFETY THERMOSTAT fixed setting, no reset SWITCHING TEMP. 110 +0/-5 °C

ROOM THERMOSTAT analog

SPST CONTACT 16 A

TEMPERATURE
ADJUSTMENT RANGE 5 - 35 °C

TEMPERATURE
ADJUSTMENT METHOD

SWITCHING DIFFERENCE


rotating knob

0,5 °C

SWITCHING DIFFERENCE 0,5 °C
IP RATING IP 20
POWER CABLE

CROSS SECTION $3 \times 0.75 \text{ mm}^2$ LENGTH 3 mCABLE GLAND Pg9

DIMENSIONS, MODELS



MODEL		Z-SKVT 300	Z-SKVT 400	Z-SKVT 500	Z-SKVT 600	Z-SKVT 700	Z-SKVT 800	Z-SKVT 900	Z-SKVT 1000	Z-SKVT 1200	Z-SKVT 1350
NOMINAL OUTPUT	W	300	400	500	600	700	800	900	1000	1200	1350
NOMINAL CURRENT	Α	1.3	1.8	2.2	2.6	3.0	3.5	3.9	4.4	5.2	5.9
ELEMENT LENGTH (L) ± 5 mm	mm	395	435	535	585	685	735	835	885	1045	1135
CODE		7573	7574	7575	7576	7577	7578	7579	7580	7581	8597