

# KPS11 SOLAR COLLECTOR



Flat plate collector of 1802 W output (at 1000 W/m<sup>2</sup> irradiance), designed for on-roof portrait installation. A harp absorber with highly selective TiNOx surface is laser welded to the copper pipes. The insulation consists of 40 mm mineral wool. Connections are located on both sides on the top and bottom.

**Code: 16278**

## DIMENSIONS AND WEIGHT

height x width x thickness	2037 x 1235 x 90 mm
total area	2.516 m <sup>2</sup>
aperture area	2.295 m <sup>2</sup>
empty weight	45 kg

## GLAZING

material	tempered prismatic glass
thickness	3.2 mm

## ABSORBER

material	Al, tl. 0.5 mm
surface finish	TiNOx
design type	harp type, laser welded
material and size of connection pipes	copper 4 x Ø 22 mm x 0.7 mm
material and size of absorber tubes	copper 11 x Ø 8 mm x 0.5 mm
max. working pressure	10 bar
max. working temperature	110 °C
stagnation temperature	200 °C
heat transfer fluid	water solution of propylene glycol, 1.71
recommended flow rate	60 - 120 l/h

## THERMAL INSULATION

insulation material	mineral wool
insulation thickness	40 mm

## FRAME

frame material	aluminum alloy
frame color	gray
rear sheet	zinc-plated steel, 0.5 mm thick

## COLLECTOR EFFICIENCY PARAMETERS RELATED TO APERTURE/TOTAL SURFACE AREA

$\eta_{0a}$	0.785 / 0.716
$a_{1a}$	4.44 / 4.05 W/m <sup>2</sup> K
$a_{2a}$	0.0068 / 0.0062 W/m <sup>2</sup> K <sup>2</sup>

## Mount and connection kits

		Code
Connection kit		7710
Kit for 1 collector	[for 4 roof anchors or 2 supports + 1 strut]	12184
Kit for 2 collectors	[for 6 roof anchors or 3 supports + 1 strut]	12185
Kit for 3 collectors	[for 8 roof anchors or 4 supports + 1 strut]	12186
Kit for 4 collectors	[for 10 roof anchors or 5 supports + 1 strut]	12187
Mount and interconnection kit for 1 collector	[for 4 roof anchors or 2 supports + 1 strut]	12188

The Connection kit contains an inlet elbow (Cu22 x 3/4" F), outlet pipe cross (Cu22 x 3/4" F + 3/8" F for an air vent valve and 1/2" F for a temperature sensor sheath), sheath with a temperature sensor and 2 straight adapters (Cu22 x 3/4" F) with a plug and gaskets.



The mount and connection kits consist of aluminum mounting rails, retaining hooks for bottom mounting rails, retaining side clamps, bolts and nuts, straight fittings (2 and more collectors) and pipe insulation.